



Preview IST - International Surface Technology 03.2024

FOCUS | PARTS CLEANING

High-purity parts cleaning - a question of requirements

The requirements for equipment, environment and cleaning media in the high-purity sector are enormous. It is important to take a look at what is meant by high purity in the industry and in the world of parts cleaning, as this varies considerably. The appropriate cleaning concept depends on this.

Dry reliably and save energy
An ageing passivation line for medical implants and instruments was replaced by a modern new system. The process steps of cleaning, passivation, rinsing and drying were analysed in terms of quality, throughput and energy savings.

NEW TECHNOLOGIES

Al in parts cleaning is making further progress

How can parts cleaning be improved with the help of artificial intelligence? A project is investigating this question: One aim is to develop a cleaning system that can control and adapt itself. The project partners have now completed important intermediate steps.

FUNCTIONAL COATINGS

Plasma technology as an alternative to electroplating?

If reliable conductivity and appropriate corrosion protection are required, precious metals are generally used. The use of atmospheric plasma technology is cheaper, more efficient and more environmentally friendly: it allows the surfaces of base metals to be treated selectively and precisely.

Dates

Advertising deadline: 08/20/2024 Copy deadline: 08/27/2024 Publication date: 09/17/2024

WET PAINTING

Cost-saving powder booth
For a plant manufacturer, a delivery
order for extra-large ultrasonic sieve
systems was the starting signal for the
step-by-step development of a complex
powder coating line including a powder
booth with high efficiency.

POWDER COATING

Cost-saving powder booth
For a plant manufacturer, a delivery
order for extra-large ultrasonic sieve
systems was the starting signal for the
step-by-step development of a complex
powder coating line including a powder
booth with high efficiency.

COATINGS

The curing oven remains switched off Polyaspartic resins have been on the market for a long time. They have a low viscosity, which enables very high solids content and even solvent-free coatings. Their high reactivity also ensures particularly fast curing. This makes them a sustainable option for users.

ROBOT PAINTING

Automated painting of agricultural machinery engines
A pool of suppliers worked together to build the new automated engine painting system for a group of companies based in Italy. An international materials handling provider took responsibility for the paint application.

CORROSION PROTECTION

Unclear salt limits make corrosion protection difficult
In order to protect steel from corrosion with coating systems and thus maintain the long-term functionality of structures, several requirements must be met. One issue that has not been conclusively clarified in specialist circles for years is the level of the limit values for salts on steel surfaces to be coated.

ROBOTICS

Cleaning technology meets robotics
Before industrially manufactured
components can be further processed
and coated, for example, they often first
have to be cleaned of oil, grease, swarf,
burrs or metal flakes from the
manufacturing process. In order to
integrate cleaning into their own
production line as efficiently as
possible, many companies rely on
automation and modern robot cells for
parts cleaning.

Contact



Maximilian Fuchs
Sales Management
+49 (0) 611.7878 146
maximilian.fuchs(at)springernature.com

ELECTROPLATING TECHNOLOGY

Platinum layers for applications ranging from hydrogen to connectors
A special electrolyte for electroplating with pure platinum opens up new possibilities. According to the supplier, it enables the deposition of exceptionally thick, homogeneous and crack-free platinum layers, which should provide advantages in various technical applications in particular.

BLASTING

Robotics in pre-treatment Robotics is increasingly finding its way into the surface pre-treatment of coatings by blasting. However, special robot technology is required for this abrasive application, as standard industrial robots are unable to perform this task.

MEASURING AND TESTING

Non-destructive testing of plastic coatings
Photothermal coating thickness measurement is a non-contact process for paints, powder coatings and glazes on a wide variety of substrates. The different thermal properties of the coating and substrate are utilised to determine the coating thickness. Three application examples show the advantages of this method.

SPRINGER NATURE

© 2024 Springerfachmedien Wiesbaden